

PROFILES and GUIDES


TECHNICAL DATA SHEET

Last Update 22-01-2020

L40 RF

DESCRIPTION

PVC inclined lateral profile, flat base without groove.



TECHNICAL SPECIFICATIONS

Material		Polyvir	ıyl ch	loride (P	VC)
Hardness				60 ±5 S	Sh.A
Colour				Gr	een
Base					Flat
B Upper base		20.0	mm	0.79	in
b Bottom base			mm		in
H Height		40.0	mm	1.57	in
Weight		378	gr/m	0.336	oz/in
Minimum pitch					
longitudinal			mm		in.
■ transversal		50	mm	2.0	in.
Minimum pulley diamete	rs ⁽¹⁾				
longitudinal-driving side			mm		ir
longitudinal-conveying side			mm		ir
transversal-conveying side		80	mm	3.2	in
(1) Minimum pulley diameters referred	d to environn	nent condition	ons of 2	0°C	
Temperature	min.	-10	°C	14	۰F
resistance (2)	max	60	°C	140	٥F
(2) Use with limit values may reduce i	ts life				
Roll/bar sizes		2.4	m	7.9	ft

COMPLIANCES

REACH EC 1907/2006 Regulation and Amendments

METHOD OF APPLICATION

- High frequency welding

NOTES

PRODUCT CODE ES105

DISCLAIMER

The information contained in this document describes the features of the CHIORINO product as tested in a laboratory environment at a temperature of +23 degrees °C at 50% relative humidity. It does not necessarily reflect the conditions of industrial use and it does not guarantee the product to be suitable for certain applications. The client remains liable for the proper selection and correct use of the CHIORINO product. CHIORINO cannot be held responsible should damages arise from the use of its products. Necessary alterations to this data can be made without prior notice.