


PROFILES and GUIDES

TECHNICAL DATA SHEET

T20 RF W

DESCRIPTION

PVC lateral profile, straight flat base without groove.



COMPLIANCES

REACH EC 1907/2006 Regulation and Amendments FDA (Food and Drug Administration)

TECHNICAL SPECIFICATIONS

rial Polyvinyl chlo	Polyvinyl chloride (PVC)		
ness 6	50 ±5	Sh.A	
ır	V	Vhite	
		Flat	
per base 20.0 mm	0.79	in.	
tom base mm		in.	
ight 20.0 mm	0.79	in.	
ht 221 gr/m	0.196	oz/in.	
num pitch			
igitudinal mm		in.	
nsversal 50 mm	2.0	in.	
num pulley diameters ⁽¹⁾			
igitudinal-driving side mm		in.	
gitudinal-conveying side mm		in.	
nsversal-conveying side 80 mm	3.2	in.	
num pulley diameters referred to environment conditions of 20°	С		
oerature min10 °C	14	٩F	
ance ⁽²⁾ max 60 °C	140	°F	
with limit values may reduce its life			
bar sizes 2.4 m	7.9) ft	

METHOD OF APPLICATION

- High frequency welding
- Hot air welding

NOTES

PRODUCT CODE ES142

Last Update 22-01-2020

DISCLAIMER

The information contained in this document describes the features of the CHIORINO product as tested in a laboratory environment at a temperature of +23 degrees °C at 50% relative humidity. It does not necessarily reflect the conditions of industrial use and it does not guarantee the product to be suitable for certain applications. The client remains liable for the proper selection and correct use of the CHIORINO product. CHIORINO cannot be held responsible should damages arise from the use of its products. Necessary alterations to this data can be made without prior notice.