


#### **PROFILES and GUIDES**

#### **TECHNICAL DATA SHEET**

# **L70 RF W**

## **DESCRIPTION**

PVC inclined lateral profile, flat base without groove.



# TECHNICAL SPECIFICATIONS

Hardness				60 ±5	Sh /
Tidi difess				00 ±3	511.7
Colour				V	/hite
Base					Flat
B Upper base		20.0	mm	0.79	in
b Bottom base			mm		in
H Height		70.0	mm	2.76	in
Weight		653	gr/m	0.581	oz/ir
Minimum pitch					
longitudinal			mm		in
■ transversal		50	mm	2.0	in
Minimum pulley diameters	S <sup>(1)</sup>				
longitudinal-driving side			mm		iı
longitudinal-conveying side			mm		iı
transversal-conveying side		80	mm	3.2	iı
(1) Minimum pulley diameters referred t	o environn	nent condition	ons of 20	D,C	
Temperature	min.	-10	°C	14	٥
resistance (2)	max	60	°C	140	٥
(2) Use with limit values may reduce its	life				
Roll/bar sizes		2.4	m	7.9	f

# **COMPLIANCES**

REACH EC 1907/2006 Regulation and Amendments FDA (Food and Drug Administration)

## **METHOD OF APPLICATION**

- High frequency welding

### **NOTES**

PRODUCT CODE ES208 Last Update 22-01-2020

## **DISCLAIMER**

The information contained in this document describes the features of the CHIORINO product as tested in a laboratory environment at a temperature of +23 degrees °C at 50% relative humidity. It does not necessarily reflect the conditions of industrial use and it does not guarantee the product to be suitable for certain applications. The client remains liable for the proper selection and correct use of the CHIORINO product. CHIORINO cannot be held responsible should damages arise from the use of its products. Necessary alterations to this data can be made without prior notice.