

PROFILES and GUIDES


TECHNICAL DATA SHEET

L70 RF

DESCRIPTION

PVC inclined lateral profile, flat base without groove.





TECHNICAL SPECIFICATIONS

Material		Polyvinyl chloride (PVC)			
Hardness				60 ±5	Sh.A
Colour				G	reen
Base					Flat
B Upper base		20.0	mm	0.79	in.
b Bottom base			mm		in.
H Height		70.0	mm	2.76	in.
Weight		653	gr/m	0.581	oz/in.
Minimum pitch					
Iongitudinal			mm		in.
transversal		50	mm	2.0	in.
Minimum pulley diameters ⁽¹⁾					
longitudinal-driving side			mm		in.
longitudinal-conveying side			mm		in.
transversal-conveying side		80	mm	3.2	in.
$^{(1)}\rm Minimum$ pulley diameters referred to environment conditions of 20°C					
Temperature	min.	-10	°C	14	°F
resistance ⁽²⁾	max	60	°C	140	°F
⁽²⁾ Use with limit values may reduce its li	fe				
Roll/bar sizes		2.4	m	7.9	ft

COMPLIANCES

REACH EC 1907/2006 Regulation and Amendments

METHOD OF APPLICATION
- High frequency welding
NOTES
NOTES
Last Update 22-01-2020

DISCLAIMER

PRODUCT CODE ES81

DISCLAIMER The information contained in this document describes the features of the CHIORINO product as tested in a laboratory environment at a temperature of +23 degrees °C at 50% relative humidity. It does not necessarily reflect the conditions of industrial use and it does not guarantee the product to be suitable for certain applications. The client remains liable for the proper selection and correct use of the CHIORINO product. CHIORINO cannot be held responsible should damages arise from the use of its products. Necessary alterations to this data can be made without prior notice.